



Specifications

Technical:

- » Inputs Tx (Each): 1 HDMI/DVI, 1 Serial IR Rx, 1 RS-232, 1 TCP/IP
- » Outputs Tx (Each): 1 CAT6 STP, 1 HDMI/DVI pass through, 1 Serial IR Tx
- » Inputs Rx (Each): 1 CAT6 STP, 1 Serial IR Rx
- » Outputs Rx (Each): 1 HDMI/DVI, 1 Serial IR Tx, 1 TCP/IP, 1 RS-232
- » HDMI® and HDCP Licensing: Fully licensed and compatible with all HDMI and HDCP technologies
- » Link and Range: 1080p/60, 1920x1200 up to 400 ft. when used with KD-CAT6STP1X cabling, 300 ft. when used with third-party CAT6/STP cabling.
- » Lossless Compressed Digital Audio Support: Dolby® TrueHD, Dolby® Digital Plus and DTS™-HD Master Audio
- » DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- » HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- » HDMI Connector: Type A, 19 Pin Female
- » RJ45 Connector: Shielded Link Connector
- » Ethernet RJ45 Connector: Shielded TCP/IP 10/100 BaseT
- » IR Connector: 3.5 mm monaural mini jack
- » RS-232 Connector: D-Sub 9 Pin
- » I2C Communication: EDID and HDCP bi-directional transparency from Display to Source
- » CEC Support: To the main input and output HDMI channel. Does not support CEC for the pass-through HDMI output.



General

- » Regulation: CE, RoHS, WEEE
- » Power: UL Certified Power Supply – 5V / 2A, 110-240 VAC, 50-60 Hz
- » Power Consumption: Tx - 2.5 Watts, Rx - 5 Watts
- » Accessories: Mounting Bracket, Locking HDMI Cable Clip
- » Product Dimensions (Each): 6" x 4.1" x 1.2"
- » Shipping Carton Dimensions: 15.4" x 8.7" x 3.6"
- » Product Weight (Each): 1 lb
- » Shipping Weight: 3 lbs
- » Enclosure:

