

Specifications

Technical:

» Inputs:

2 Component, Y/G, Pb/B, Pr/R or RGB (progressive and interlaced) 1Vpp/75Ω on RCA connectors; Same connectors can be re-used for Composite or S-Video.

2 Left and Right Stereo Pairs or Horizontal and Vertical Sync, 2Vp-p, 10KΩ on RCA connectors;

2 S/PDIF 1Vpp/75Ω on RCA connector.

» Outputs:

1 Component, Y/G, Pb/B, Pr/R or RGB (progressive and interlaced) 1Vpp/75Ω on RCA connectors; Same connectors can be re-used for Composite or S-Video.

1 Left and Right Stereo Pair or Horizontal and Vertical Sync, 2Vp-p, 10KΩ on RCA connectors;

1 S/PDIF 1Vpp/75Ω on RCA connector.

» **Input/Output Resolutions:** Any resolution from 480i to 1080p

» **Bandwidth:** -3 dB @ 300 MHz, linear phase pass band

» **Control:** Front panel touch switch and LED's, IR remote control.

» **Power:** External Power Supply. 6V / 5A, 110-120 VAC, 60HZ.

General

» **Regulation:** CE, RoHS, WEEE

» **Rack Mount:** Shelf Mountable. Rack Ears Not Included.

» **Enclosure:** Black Metal

» **Product Dimensions:** L = 8.5" W = 4.25" H = 1.75"

» **Shipping Carton Dimensions:** L = 13.5" W = 7" H = 4.5"

» **Product Weight:** 1.75 lbs

» **Shipping Weight:** 3 lbs

» **Accessories:** IR Remote Control, UL Certified Power Supply