

Specifications

Technical:

» Inputs:

4 Component, Y/G, Pb/B, Pr/R or RGB (progressive and interlaced), 1Vpp/75Ω on RCA connectors; Same connectors can be re-used for Composite or S-Video.

4 Left and Right Stereo Pairs or Horizontal and Vertical Sync, 2Vp-p, 10KΩ on RCA connectors; 4 S/PDIF 1Vpp/75Ω on RCA connector.

» Outputs:

1 Component, Y/G, Pb/B, Pr/R or RGB (progressive and interlaced), 1Vpp/75Ω on RCA connectors; Same connectors can be re-used for Composite or S-Video.

1 Left and Right Stereo Pair or Horizontal and Vertical Sync, 2Vp-p, 10KΩ on RCA connectors; 1 S/PDIF 1Vpp/75Ω on RCA connector.

» Input/Output Resolutions: Any resolution from 480i to 1080p

» Bandwidth: -3 dB @ 300 MHz, linear phase pass band

» Control: Front panel touch switch and LED's, IR remote control, RS-232

» Power: External Power Supply. 6V / 5A, 110-120 VAC, 60 Hz

General

» Regulation: CE, RoHS, WEEE

» Rack Mount: 1U, rack ears included

» Enclosure: Black Metal

» Product Dimensions: L = 17.25" W = 4.5" H = 1.75"

» Shipping Carton Dimensions: L = 23.5" W = 7" H = 4.5"

» Product Weight: 4 lbs

» Shipping Weight: 6 lbs

» Accessories: IR Remote Control, UL Certified Power Supply